



PROJECT NAME: havana music lounge

SPECIFIER: gss

CLIENT: jeff

REGION: durban

DATE: 22-3-2013

YOUR SPECIFICATION

RANGE: GYPROC GYPWALL INTERNAL WALL SYSTEMS



**WALL SURFACE
FINISH**


RhinoLite Multipurpose



FIRE RATING
60 minutes



SOUND RATING
Rw 49dB



SYSTEM
GypWall FireStop 51/F60S49

Gyproc 2700mm high GypWall FireStop (Rw 49dB - 60 minutes fire rating) Ultrasteel Stud Drywall, consisting of stud and track system with 51 x 35mm Drywall Ultrasteel studs at 600mm centres friction fitted into head track and floor track with 63mm "Cavitybatt" insulation inserted into cavity of partitioning and clad on both sides with 15mm thick FireStop board fixed at 220mm centres using 25mm RhinoBoard Sharp Point Screws with all external angles to have Drywall cornerbeads attached and all joints to be covered with RhinoTape. Wall surface to be finished with minimum 3mm thick RhinoLite Multipurpose, all in accordance with the manufacturer's recommendations.

- Wall system : GypWall FireStop 51/F60S49
- Cladding : Rhinoboard Firestop board
- Stud size : 51 x 35mm
- Fire rating : 60 minutes
- Sound rating : Rw 49dB.

For more detail contact our Technical and Specifications Department.

Ph: 0860 262 728

Email: talk2gyproc@saint-gobain.com